

## Inside Screw Gate Valves

Inside screw gate valves are used underground with indicator posts attached or as roadway box valves (curb box installation). FM Approved valves are available with a variety of end connections as indicated in the listings.

Valves having Ring-Tite, Fluid-Tite or Tyton-Joint connections should be anchored in place during installation. Unless otherwise noted in the listing, these valves have 175 psi (1205 kPa) rated working pressure.

### Model 5200, 2010FF, 2010FM, 2010MM

<i>Model No.</i>	<i>Description</i>	<i>Size, in. (mm) (NPS)</i>	<i>Max Working Pressure, psi (kPa)</i>	<i>End Connections</i>
"United" 5200*	Resilient Seated Gate Valve	2-1/2, 3, 4, 6, 8, 10, 12 (65, 80, 100, 150, 200, 250, 300)	200 psi (1380 kPa)	Flange × Flange (ANSI, BS10, BS4505, JIS B2212, JIS B2213)
"United" 2010FF *	Resilient Seated Gate Valve	4, 5, 6, 8, 10, 12 (100, 125, 150, 200, 250, 300)	250 psi (1720 kPa)	Flange × Flange (ANSI, ISO, JIS)
"United" 2010FM *	Resilient Seated Gate Valve	4, 5, 6, 8, 10, 12 (100, 125, 150, 200, 250, 300)	250 psi (1720 kPa)	Flange × Mechanical Joint
"United" 2010MM *	Resilient Seated Gate Valve	4, 5, 6, 8, 10, 12 (100, 125, 150, 200, 250, 300)	250 psi (1720 kPa)	Mechanical Joint

\*Available with or without indicator post flange.

<b>Company Name:</b>	Linx Limited
<b>Company Address:</b>	875 Aquidneck Ave, Middletown, Rhode Island 02842, USA
<b>Company Website:</b>	Not Available
<b>Listing Country:</b>	United States of America
<b>Certification Type:</b>	FM Approved